

## Feature:

- Silicone extrusion process, high color consistency, short lead-time
- Independent wire power supply, low voltage drop
- LED light source, low energy consumption, long lifespan
- Flexible body, furace corner is unlimited
- Without lead, mercury and other elements, green environmental protection
- Light is soft&uniform, without light points



## Product parameters:

Code	NFSP12X
Light Source	SMD2835
Lumen/led	20-22LM/LED
LED Quantity	120LEDs/Meter
Beam Angle	160°
LED Color CCT	Warm White/White (Jacket orange/purple/light pink/lemon yellow/green/ice blue/red/blue/yellow/pink/white)
LED Lifetime	>50,000hrs
PCB Color	White double side ,single row PCB
Cover	Silicone glue
Warranty	indoor is 2 years , outdoor is 1 year
<b>Mechanical Characteristics:</b>	
Method of Installation	Easy to install by clip
Dimension	6*12mm
Waterproof type	IP65 (MIDDLE OF LED NEON)*
Package:	10 meter/roll
<b>Electrical Characteristics:</b>	
Wattage	MAX 8W/M
Input Voltage	DC12V Cuttable :each 2.5 CM / 1 CM
<b>Temperature Range:</b>	
Ambient Temperature	( -40°C - 60°C )
Working Temperature	( -20°C - 40°C )
<b>Product Features:</b>	
Energy Savings	Saving 50%-80% energy
Long Lasting	More than 50.000 hours working lifetime
Eco-friendly	No RF interference, no Mercury or Lead
Main materials	PCB(ROLLED ANNEAL Copper Foil)
Certification	RoHS and CE

\* The product once cut loses the IP and the guarantee.